F**;;**RTINET

FortiGate[®]-800C

Accelerated Security for Mid-Sized Enterprises and Large Branch Offices

FortiGate Unified Threat Management (UTM) systems from Fortinet® offer you the freedom to select the security solution that most closely matches your port density, performance, and bandwidth needs. With firewall performance of 20 Gbps and IPS throughput of 6 Gbps and 10-GbE interfaces in a 1U form-factor, FortiGate-800C is ideal for mid-sized enterprises and large enterprise branch offices. The FortiGate-800C platform gives you the ability to improve your security posture and accelerate your network performance while simplifying your network infrastructure.

The Power of Unified Threat Management

Like other members of the FortiGate product family, the FortiGate-800C combines firewall, application control, IP Sec and SSL VPN, intrusion prevention, antivirus, antimalware, antispam and Web filtering into a single device. Equipped with these broad security capabilities, the FortiGate-800C can help organizations meet regulatory compliance requirements and protect against the latest targeted attacks, network vulnerabilities and malicious applications.

The FortiGate-800C supports today's advanced networks with with two (2) 10-GbE and twelve (12) 10/100/1000 interfaces that can be easily partitioned into independent security zones and custom combinations of LAN and WAN ports. Eight (8) shared copper/fiber GbE interfaces support evolving networks that may be migrating to fiber on select network segments. You can protect your network availability with two (2) pairs of bypass-enabled ports, allowing continued network operations in the event of device failure. Dual-WAN redundant connections for maximum reliability and availability are also supported by default and a dedicated DMZ port adds an extra layer of protection for Web-facing servers. The onboard USB management port provides an easy way to setup and configure the device using the FortiExplorer configuration wizard. In addition, the FortiGate-800C features 64 GB of internal storage for WAN optimization, local SQL-based reporting, or data archiving for policy compliance.



FortiOS 4.3: Redefining Network Security

FortiOS 4.3 is the software foundation of FortiGate multi-threat security platforms. Developed solely for security, performance and reliability, it is a purpose-built operating system that leverages the power of the FortiASIC content and network processors. FortiOS software enables a comprehensive suite of security services: Firewall, VPN, intrusion prevention, antivirus/ antispyware, antispam, web filtering, application control, data loss prevention, and end point network access control.

The FortiASIC Advantage

FortiASIC processors power FortiGate platforms. With exclusive hardware, the purpose built, high performance Network, Security, and Content processors use intelligent and proprietary digital engines to accelerate resource intensive security services.

Challenge	Solution
Visibility and control of new applications and content	FortiGate devices deliver complete, comprehensive application control, enabling you to block unwanted traffic and behavior.
Time-sensitive applications require extremely low latency during transit	FortiGate-800C appliance ensures that security is never a bottleneck. Up to 20 Gbps firewall performance and up to 8 Gbps IPSec VPN performance ensures optimal performance of latency-sensitive applications.
Internal network segmentation is difficult to deploy	FortiGate-800C appliance with 24 hardware-accelerated switched ports permit a wide-array of deployments.
Evolution of network infrastructure	The FortiGate-800C includes 2 10-GbE interfaces for maximum performance, as well as shared media interfaces to ease the transition from copper to fiber.
Eliminating blind spots caused by using multiple non-integrated security technologies	Fortinet combines core security technologies such as firewall, VPN, intrusion prevention, and application control into a single platform, providing an effective all-in-one solution.

FortiGate Consolidated Security Solutions

Fortinet's consolidated security solutions provide you with an integrated set of core security and network services in a single, easy-to-manage, high-performance appliance that gives you unmatched flexibility to deploy the right mix of technology for your unique requirements. In addition, FortiGuard[®] Subscription Services include dynamic updates to ensure your security environment remains current and your corporate resources are protected against the latest threats.

Technical Specifications	FortiGate-800C
HARDWARE	
Accelerated 10-GbE SFP+ Interfaces	2
Accelerated 10/100/1000 Interfaces (RJ-45)	12
Accelerated GbE SFP or 10/100/1000 Shared Interfaces	8
Accelerated 10/100/1000 Bypass Interfaces	2 pairs
10/100/1000 Management Interface	2
Maximum Network Interfaces	26
Internal Storage	64 GB
USB Ports (Client/Server)	1/1
SYSTEM PERFORMANCE	
Firewall Throughput (1518 / 512 / 64 byte UDP packets)	20 / 20 / 20 Gbps
Firewall Latency (64 byte UDP packets)	6 µs
Firewall Throughput (Packets Per Second)	31 Mpps
Concurrent Sessions (TCP)	7 M
New Sessions/Sec (TCP)	190,000
Firewall Policies (System / VDOM)	100,000 / 50,000
IPSec VPN Throughput (512 byte packets)	8 Gbps
Gateway-to-Gateway IPSec VPN Tunnels (System / VDOM)	10,000 / 5,000
Client-to-Gateway IPSec VPN Tunnels	50,000
SSL-VPN Throughput	1 Gbps
Concurrent SSL-VPN Users (Recommended Max)	1,000
IPS Throughput	6 Gbps
Antivirus Throughput (Proxy Based / Flow Based)	1.7 / 2.1 Gbps
Virtual Domains (Default / Max)	10 / 10
Max Number of FortiAPs	512
Max Number of FortiTokens	1,000
Max Number of FortiClients	3,000
High Availability Configurations	Active/Active, Active/ Passive, Clustering
Unlimited User Licenses	Yes
Ordering Info	
Unit	
FortiGate-800C	
Optional Accessories	

Technical Specifications	FortiGate-800C	
DIMENSIONS AND POWER		
Height	1.75 in (44 mm)	
Width	17 in (432 mm)	
Length	16.42 in (417 mm)	
Weight	18.8 lb (8.5 kg)	
Rack Mountable	Yes (Attachable Ears)	
AC Power	100-240 VAC, 60-50 Hz	
Power Consumption (AVG)	158 W	
Power Consumption (Max)	189 W	
Heat Dissipation	645 BTU/h	
Redundant Power Supply (Hot-swappable)	Optional	
ENVIRONMENT AND CERTIFICATIONS		
Operating temperature	32 - 104 °F (0 - 40 °C)	
Storage temperature	-13 - 158 °F (-25 - 70 °C)	
Humidity	20 to 90% non-condensing	
Compliance	FCC Part 15 Class A, C-Tick, VCCI, CE, UL/CUL, CB	
Certifications	ICSA Labs: Firewall, IPSec, IPS, Antivirus, SSL VPN	

All performance values are "up to" and vary depending on system configuration. Antivirus performance is measured using 44 Kbyte HTTP files. IPS performance is measured using 1 Mbyte HTTP files.

Ordering Info	
Unit	SKU
FortiGate-800C	FG-800C
Optional Accessories	SKU
FG-600C, FG-800C and FG-1000C AC Power Supply	SP-FG600C-PS

FortiGuard[®] Security Subscription Services deliver dynamic, automated updates for Fortinet products. The Fortinet Global Security Research Team creates these updates to ensure up-to-date protection against sophisticated threats. Subscriptions include antivirus, intrusion prevention, web filtering, antispam, vulnerability and compliance management, application control, and database security services.

FortiCare[™] Support Services provide global support for all Fortinet products and services. FortiCare support enables your Fortinet products to perform optimally. Support plans start with 8x5 Enhanced Support with "return and replace" hardware replacement or 24x7 Comprehensive Support with advanced replacement. Options include Premium Support, Premium RMA, and Professional Services. All hardware products include a 1-year limited hardware warranty and 90-day limited software warranty.

FRTINET

GLOBAL HEADQUARTERS

Fortinet Incorporated 1090 Kifer Road, Sunnyvale, CA 94086 USA Tel +1.408.235.7700 Fax+1.408.235.7737 www.fortinet.com/sales

EMEA SALES OFFICE – FRANCE Fortinet Incorporated 120 rue Albert Caquot 06560, Sophia Antipolis, France Tel +33.4.8987.0510 Fax +33 4.8987.0511

APAC SALES OFFICE – SINGAPORE Fortinet Incorporated 300 Beach Road #20-01, The Concourse Singapore 199555 Tel: +65-6513-3734 Fax: +65-6295-0015



Copyright© 2012 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, and FortiGuard®, are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance metrics contained herein were attained in internal lab tests under ideal conditions, and performance may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Coursel, with a purchaser that expressly warrants that the identified product will perform according to the performance metrics herein. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any guarantees. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.